

750II MONITOR/CONTROLLERS PRICE LIST

Conductivity/TDS and Resistivity

JANUARY 1, 2017



| <u>MODEL</u> | <u>CONDUCTIVITY/TDS</u> | <u>PRICE</u> |
|--------------|----------------------------------|--------------|
| 756II..... | Analog Monitor only | \$602.50 |
| 757II..... | Analog Monitor/controller | \$693.50 |
| 758II..... | Digital Monitor/controller | \$657.50 |
| 759II..... | Digital Monitor only..... | \$567.50 |

RESISTIVITY

| | | |
|------------|----------------------------------|----------|
| 751II..... | Analog Monitor only | \$619.50 |
| 752II..... | Analog Monitor/controller | \$711.00 |
| 753II..... | Digital Monitor/controller | \$676.00 |
| 754II..... | Digital Monitor only..... | \$586.00 |

RANGE (Must select range; see 750II Range Selection Guide.)

Add to above model number as shown in example: 751II-11 No additional charge

OPTIONS

| | | |
|------------|---|----------|
| -SC..... | Second Alarm/control Module (Monitor/controllers only) | \$161.50 |
| -4A..... | 4-20 mA Self-Powered Isolated Output Module (digital models only) | \$182.00 |
| -PA..... | ~70dB Piezo Electric Alarm (mounted on front panel) (digital Monitor/controllers only) | \$54.50 |
| -PAT..... | ~70dB Piezo Alarm and Timer Module (digital Monitor/controllers only) | \$191.00 |
| -35BL..... | 3½ Digit Backlit Liquid Crystal Display (LCD) | \$151.00 |
| -45BL..... | 4½ Digit Backlit Liquid Crystal Display (LCD) | \$182.00 |
| -TP | Temperature Module 0-200°C, requires -TP sensor (digital models only) | \$212.00 |
| -TH | TP/TPO Alarm/control Harness (requires SC & TP above) (digital Monitor/controllers only) | \$82.00 |
| -PC..... | Power Cord 115 VAC (8 ft./2,44 meters with plug and strain relief) | \$34.00 |

SPECIAL ORDER OPTIONS

| | | |
|------------|---|----------|
| -24VA..... | 24 VAC Isolated Power Supply | \$28.50 |
| -PTS..... | Panel mounted full scale test switch..... | \$65.00 |
| -SFP..... | Panel mounted set point adjustment (digital Monitor/controllers only)..... | \$85.00 |
| -TPA..... | Temperature Module 0-200°C, above -TP with adjustable hysteresis (digital models only) | \$215.50 |
| -HT..... | High Temperature modification for -HT sensors, range limited (contact Myron L technical sales) | \$69.50 |

Order Example: For a Digital 0-5000 µS Conductivity Monitor/controller with 4-20 and 4½ digit backlit display:

| MODEL | RANGE | OPTIONS | TOTAL PRICE |
|-------------|-----------|---------------|-------------|
| 758II | -123..... | -4A-45BL..... | \$1021.50 |

ACCESSORIES

| <u>MODEL</u> | <u>DESCRIPTION</u> | <u>PRICE</u> |
|--------------|--|--------------|
| SCO..... | Second Alarm/control Module with harness (Monitor/controllers only) | \$161.50 |
| 4AO | 4-20 mA Self-Powered Isolated Output Module with harness (digital models only) | \$182.00 |
| 3SE..... | 3 Sensor Input Module with Enclosure..... | \$265.00 |

Continued

ACCESSORIES *Continued*

| MODEL | DESCRIPTION | PRICE |
|--------------------|--|--------------|
| 3SO | 3 Sensor Input Module with 1 meter/3 ft. cable (customer installed)* | \$142.00 |
| 3RE | 3 Range Switch with Enclosure (Add C=Cond or R=Res)..... | \$265.00 |
| 3RO | 3 Range Switch with 1 meter/3 ft. cable (Add C=Cond or R=Res)* | \$142.00 |
| 3SRE | Above 3S and 3R combined with Enclosure (Add C=Cond or R=Res) | \$299.00 |
| 3SRO | Above 3S and 3R combined (Add C=Cond or R=Res)* | \$193.50 |
| PAO | ~70dB Piezo Electric Alarm only (digital Monitor/controllers only) | \$54.50 |
| PATO | ~70dB Piezo Alarm and Timer Module (digital Monitor/controllers only)..... | \$191.00 |
| 35BLO | 3½ Digit Backlit Liquid Crystal Display (LCD) | \$243.50 |
| 45BLO | 4½ Digit Backlit Liquid Crystal Display (LCD) | \$273.00 |
| TPO | Temperature Module 0-200°C, requires -TP sensor with harness (digital models only) | \$212.00 |
| THO | TP/TPO Alarm/control Harness only (requires SCO and TPO above)..... | \$82.00 |
| TPC | Calibration Module (temperature module) | \$180.00 |
| PCO..... | Power Cord 115 VAC (8 ft./2,44 meters with plug and strain relief) - NOT for 230 VAC use | \$27.50 |
| SMP50..... | Surface Mounting Plate..... | \$30.50 |
| RA..... | Remote Alarm™ (Monitor/controllers only) | \$251.00 |
| VR..... | Power Supply, 115 VAC to 24 VAC, 20 VA. (indoor use only) | \$53.50 |
| 024-1 | 1 in. NPT 24 VAC Solenoid Valve | \$227.50 |
| CS-11..... | 20 Megohms Resistivity Calibration Module (sensor substitute) NIST Traceable..... | \$59.50 |
| CS-14 | 2 Megohms Resistivity Calibration Module (sensor substitute) NIST Traceable..... | \$59.50 |
| CS-17 | 200 Kilohms Resistivity Calibration Module (sensor substitute) NIST Traceable..... | \$59.50 |
| CSC | NIST Certificate for Calibration Module (sensor substitute) | NET \$41.00 |
| CC or RC..... | NIST Certificate without sensor (C=Cond or R=Res) | NET \$56.50 |
| CCATF or RCATF.... | NIST Certificate without sensor, ordered after instrument has shipped (C=Cond or R=Res)..... | NET \$88.00 |
| CCS..... | NIST Certificate with sensor, using standard solution (Conductivity/TDS only) | NET \$127.50 |

* Does not fit into enclosure, must be mounted separately.

Note: For sensor selection, see 750II Sensor Selection Guide.

Custom and OEM Monitor/controllers available, contact us with your special needs. Price and delivery upon request.

TERMS AND CONDITIONS *(Additional information upon request)*

All special order items are non-returnable and non-refundable.

Minimum order \$25.00. All prices are US dollars and are F.O.B Carlsbad, CA.

Terms: 1% 10 days, net 30 days on approved credit.

Credit Cards accepted: Visa, MasterCard, American Express, and Discover

Because of our policy of continuous product improvement, the Myron L® Company reserves the right to make changes in design, specifications, and prices without notice.

2450 Impala Drive
Carlsbad, CA 92010-7226 USA
Tel: +1-760-438-2021
Fax: +1-800-869-7668 / +1-760-931-9189
www.myronl.com

Built On Trust. Founded in 1957, the Myron L® Company is one of the world's leading manufacturers of water quality instruments. Because of our commitment to product improvement, changes in design and specifications are possible. You have our assurance any changes will be guided by our product philosophy: accuracy, reliability, and simplicity.

