

750II SENSOR SELECTION GUIDE

Conductivity/TDS, and Resistivity Monitor/controllers



- FEATURES
- WITH T-FITTING (BY CUSTOMER)

INSERTION

SUBMERSION

FLOW THROUGH

LOW RANGE
(K-0.05 & 0.1)

MEDIUM RANGE
(K-1.0)

HIGH RANGE
(K-10.0)

MAX PRESSURE
& TEMPERATURE

KEY FEATURES

Model	Image	Insertion	Submersion	Flow Through	Low Range	Medium Range	High Range	Max Pressure & Temperature	Key Features
CS10 CS10LS 316SS TEFLON®*		3/4" NPT STD ● 1/2" NPT OPT	●	●	●			100 psi/6,9 bar at 100°C/212°F	High Purity Water
CS40 CS40HT <i>(Temporarily unavailable; contact manufacturer)</i> 316SS TEFLON®*	 Shown w/optional wet-tap valve & junction box.	3/4" NPT ● 1" NPT VALVE	●	●	●	●	●	100 psi/6,9 bar at 120°C/248°F	Valve Insertable Wide Range of Measurement
CS41 CS41HT 316SS TEFLON®*		3/4" NPT ●	●	●	●	●		100 psi/6,9 bar at 150°C/302°F 250 psi/17,2 bar at 205°C/401°F (HT OPTION) 400 psi/27,6 bar at 100°C/212°F	Boiler & Condensate Service
CS50 316SS CPVC		1" NPT ●	●	●	●	●		100 psi/6,9 bar at 95°C/203°F	Low Cost
CS51 CS51LC CS51LS CS51R 316SS, TEFLON®*		3/4" NPT STD ● 1/2" NPT OPT	●	●	●	●		100 psi/6,9 bar at 100°C/212°F	Low Cost Small Size
CS52 316SS CPVC/ TEFLON®*/ KYNAR®**		3/4" NPT ●		●			●	100 psi/6,9 bar at 95°C/203°F	High Range Low Cost
CS60 316SS TEFLON®*/ KYNAR®**		1" NPT ●	●	●	●	●		100 psi/6,9 bar at 120°C/248°F	Excellent Chemical Resistance
CSA CSATC CSAR 316SS ABS PLASTIC		3/4" NPT ●		●		●		75 psi/5,2 bar at 60°C/140°F	Extremely Low Cost
Sanitec Fitting Option All CS10 & CS51 MODELS 316SS - TEFLON®*		MULTIPLE SIZES AVAILABLE ●		●	●	●		100 psi/6,9 bar at 120°C/248°F	Sanitec Fitting excellent for sanitary applications

* Teflon® is a registered trademark of DuPont.

** Kynar® is a registered trademark of Atochem.

2450 Impala Drive
Carlsbad, CA 92010-7226 USA
Tel: +1-760-438-2021
Fax: +1-800-869-7668 / +1-760-931-9189
www.myronl.com

Built On Trust. Founded in 1957, the Myron L® Company is one of the world's leading manufacturers of water quality instruments. Because of our commitment to product improvement, changes in design and specifications are possible. You have our assurance any changes will be guided by our product philosophy: accuracy, reliability, and simplicity.

MYRON L®
COMPANY
Water Quality Instrumentation
Accuracy • Reliability • Simplicity